

## Features

### Regulated Converters

- DIP24 Low Profile Miniature Package
- 1kVDC Isolation
- Feedback Regulated Output
- 2:1 Wide Range Voltage Input
- Continuous Short Circuit Protection
- Less than 7mm Height
- SMD Pinning Option
- Efficiency to 87%

### Description


The RW-S series with 2:1 input voltage ranges and max. height of 7,0 mm has been designed for the industrial automation markets. They are aimed at applications where pcb-space is at a premium so SMD pinning is also available. The converters supply the full 3 watts without additional heat-sinks over the temperature range -40°C to +80°C.

### Selection Guide

Part Number DIP24 Miniature	Input Voltage (VDC)	Output Voltage (VDC)	Output Current (mA)	Efficiency (%)
RW-053.3S	4.5 – 9	3.3	650	68
RW-0505S	4.5 – 9	5	600	69
RW-0509S	4.5 – 9	9	333	70
RW-0512S	4.5 – 9	12	250	72
RW-0515S	4.5 – 9	15	200	73
RW-123.3S	9 – 18	3.3	650	70
RW-1205S	9 – 18	5	600	73
RW-1209S	9 – 18	9	333	78
RW-1212S	9 – 18	12	250	79
RW-1215S	9 – 18	15	200	79
RW-243.3S	18 – 36	3.3	650	75
RW-2405S	18 – 36	5	600	78
RW-2409S	18 – 36	9	333	82
RW-2412S	18 – 36	12	250	84
RW-2415S	18 – 36	15	200	85
RW-483.3S	36 – 72	3.3	650	73
RW-4805S	36 – 72	5	600	78
RW-4809S	36 – 72	9	333	82
RW-4812S	36 – 72	12	250	84
RW-4815S	36 – 72	15	200	85

\* add suffix "/SMD" for SMD package, e.g. RW-2405S/SMD

## RW-05xx types



## ECONOLINE

DC/DC-Converter


RECOM

3 Watt

DIP24/SMD

Low Profile  
Package

Single Output



EN-60950-1 Certified

**RW-S**


Refer to Application Notes

www.recom-electronic.com

**Specifications (Core Operating Area)**


Input Voltage Range		2:1	
Output Voltage Accuracy		±2% max.	
Line Voltage Regulation		±0.2% typ.	
Load Voltage Regulation (10% to 100% full load)		±0.5% max.	
Output Ripple and Noise (20MHz limited)		70mVp-p max.	
Operating Frequency		85kHz min. / 100kHz typ.	
Efficiency at Full Load		See Selection Guide	
No Load Power Consumption		250mW max.	
Isolation Voltage	(tested for 1 second)	1000VDC min.	
Rated Working Voltage	(long term isolation)	see Application Notes	
Isolation Capacitance		40pF min. / 60pF max.	
Isolation Resistance		1 GΩ min.	
Short Circuit Protection		Continuous	
Operating Temperature Range (free air convection)		-40°C to +80°C (see Graph)	
Storage Temperature Range		-55°C to +125°C	
Relative Humidity		95% RH	
Package Weight	DIP24	7g	
	SMD	7.7g	
Packing Quantity		15 pcs per Tube	
MTBF (+25°C)	} Detailed Information see Application Notes chapter "MTBF"	using MIL-HDBK 217F	1034 x 10 <sup>3</sup> hours
(+80°C)		using MIL-HDBK 217F	186 x 10 <sup>3</sup> hours

**Derating-Graph**  
(Ambient Temperature)




**Typical Performance**

**RW-1205S**





**RW-2412S**





### Package Style and Pinning (mm)



#### 24 PIN DIP Miniature Package Style



#### Recommended Footprint Details







#### Pin Connections

Pin #	Single
1 & 24	+Vin
10 & 15	-Vout
11 & 14	+Vout
12 & 13	-Vin

NC = No Connection  
 XX.X ± 0.5 mm  
 XX.XX ± 0.25 mm

#### 24 PIN SMD Miniature Package Style



#### Pin Connections

Pin #	Single
1 & 24	+Vin
10 & 15	-Vout
11 & 14	+Vout
12 & 13	-Vin
others	NC

NC = No Connection  
 XX.X ± 0.5 mm  
 XX.XX ± 0.25 mm